



SPECIFICATIONS	
Technology	High intensity LED
Weight	2.2kg
Screen Impact Resistance	IK10 – BS EN50102 (single impact)
Housing Material	ADC 12 (High Pressure Aluminium Die Cast)
Paint Finish	Exterior Grade UV Resistant Polyester Powder Coat
Operating Temperature	-30°C to +60°C
Power Supply	48V ac
Current Drain	220mA Nominal
Dimming	20% of the nominal bright intensity
EMC Specification	EN50293
Fixing Centres	125mm

APPLICATIONS

- Pedestrian control
- Pedestrian & cycle control

Owing to the Company's policy of continuous improvement, AGD Systems Limited reserves the right to change their specification or design without notice. AGD products should be installed by a competent person.

PRODUCT VARIANTS	
924-181-000	PIKE LED WAIT / 12V / Dual legend / Moving Push Button
924-680-000	LED WAIT / 48V / Dual legend / Moving push button / ELV+DCM
924-680-TRS	LED WAIT / 48V / Dual legend / Moving push button / ELV+DCM C/w Tactile RHS & Sounder
924-681-000	LED WAIT / 48V / Welsh/English Dual legend / Moving push button/ELV+DCM
924-682-000	LED WAIT / 48V / Toucan legend / Moving push button / ELV+DCM
924-683-000	LED WAIT / 48V / Welsh/English Toucan legend / Moving push button/ELV+DCM
924-684-000	LED WAIT / 48V / Triple legend / Moving push button / ELV+DCM

