



SPECIFICATIONS	
Technology	High intensity LED
Weight	1.6kg
Screen Impact Resistance	IK10 – BS EN 50102 (single impact)
Housing Material	Die-cast aluminium alloy
Paint Finish	Exterior grade UV resistant polyester powder coat
Indicator Colour	Red to BS EN 12368
Operating Temperature	-30°C to +60°C
Power Supply	48Vac (12Vdc 941 option available)
Power	4.3W Bright 2.3W Dim @48V ac
Nominal Wattage (As per Elecon Code*)	4.0W
Dimming	20% of the nominal normal intensity
Rotational Pole Adjust	±15° Rotational
Fixing Centres	50mm
MTBF	>20 years based on field data from 10000 units installed over 4 years
Approved to	BS EN 50293 / TR2511

APPLICATIONS

- Pedestrian Control



Owing to the Company's policy of continuous improvement, AGD Systems Limited reserves the right to change their specification or design without notice. AGD products should be installed by a competent person.

PRODUCT VARIANTS	
941-160-000	Demand unit / 12V / Moving push button
941-660-000	Demand unit / 48V / Moving push button
941-660-OTL	Demand unit / 48V / Tactile LHS / Moving push button
941-660-OTR	Demand unit / 48V / Tactile RHS / Moving push button
941-660-TLS	Demand unit / 48V / Tactile LHS+Sounder RHS/ Moving push button
941-660-TRS	Demand unit / 48V / Tactile RHS+Sounder LHS/ Moving push button
941-661-000	Demand unit / 48V / Non moving push button
941-662-000	Demand unit / 48V / Welsh/English / Moving push button
941-664-000	Demand unit / 48V / No legend / Moving push button

