



SPECIFICATIONS	
Technology	High intensity LED
Weight	4.9kg
Screen Impact Resistance	IK10 – BS EN 50102 (single impact)
Housing Material	Die-cast aluminium alloy
Paint Finish	Exterior grade UV resistant polyester powder coat
Signal Colour	Meets requirement of BS EN 12368 Signal uniformity < 2:1
Operating Temperature	-30°C to +60°C
Power Supply	48Vac (12V dc 946 option available)
Power	Bright – Green 15W Red 10W Dim – Green 3.8W Red 2.0W
Nominal Wattage (as per Exelon Code*)	Puffin 13.0W Toucan 16.0W
Dimming	20% of the nominal normal intensity
Rotational Pole Adjust	±15° Rotational
Fixing Centres	200mm
MTBF	20 years based on field data from 3000 units installed over 5 years
Approved to	BS EN 50293 / TR2511

Owing to the Company's policy of continuous improvement, AGD Systems Limited reserves the right to change their specification or design without notice. AGD products should be installed by a competent person.

PRODUCT VARIANTS	
949-660-000	Pegasus combined NSS & demand/ 48V / Standard optics / Moving push button
949-661-000	Pegasus combined NSS & demand / 48V / Standard optics / Non moving push button
949-662-000	Pegasus combined NSS & demand/ 48V / NFOV optics / Moving push button

APPLICATIONS

- Pedestrian Control

